

Issue Date: 01-Jan-2008

Revision Date: 17-Apr-2023

Version 4

1. IDENTIFICATION

Product identifier

Product Name Peel Away® 1 Paint Remover

Other means of identification

SDS # DCI-009R

UN/ID No UN1823

Recommended use of the chemical and restrictions on use

Recommended Use Paint remover

Details of the supplier of the safety data sheet

Supplier Address

Dumond, Inc.
253 S. Bailey Road
Downingtown, PA 19335

Emergency telephone number

Company Phone Number 1-609-655-7700
Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance: Light Grey Paste

Physical state: Paste

Odor: None

Classification

Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1

Signal Word

Danger

Hazard statements

Causes severe skin burns and eye damage



Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Immediately call a poison center or doctor/physician

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a poison center or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a poison center or doctor/physician

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Calcium Hydroxide	1305-62-0	25-30
Sodium hydroxide	1310-73-2	5-10
Silica, Quartz	14808-60-7	0.001-0.5

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures**

Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a physician immediately.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention if irritation occurs.
Inhalation	Remove to fresh air. Immediate medical attention is required.
Ingestion	Rinse mouth. Do NOT induce vomiting. If conscious, give water or milk. Get medical attention if necessary.

Most important symptoms and effects, both acute and delayed

Symptoms	May cause severe chemical burns with reddening and pain. May cause dermatitis or irritation in some individuals upon prolonged contact. May cause irritation to the mucous membranes and upper respiratory tract. Ingestion may cause severe burns to mouth, throat or stomach.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically. Individuals with chronic respiratory or skin diseases may be at risk from exposure.
---------------------------	--

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

At elevated temperatures, containers may rupture. Contents are corrosive and all personal contact must be avoided.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not allow into any sewer, on the ground or into any body of water. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal. Wash spill area with plenty of water. Spills and releases may have to be reported to Federal and/or local authorities. See section 15.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a cool, well ventilated area away from acids and other incompatible substances. Store locked up.

Incompatible Materials Acids. Organic halogen compounds. Nitromethane. Flammable liquid. Metals such as aluminum, tin, and zinc.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Hydroxide 1305-62-0	TWA: 5 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ not in effect as a result of reconsideration	TWA: 5 mg/m ³
Sodium hydroxide 1310-73-2	Ceiling: 2 mg/m ³	TWA: 2 mg/m ³ (vacated) Ceiling: 2 mg/m ³	IDLH: 10 mg/m ³ Ceiling: 2 mg/m ³
Silica, Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Appropriate engineering controls**Engineering Controls**

Apply technical measures to comply with the occupational exposure limits. Use in a well-ventilated location (eg. local exhaust ventilation, fans). Showers. Eyewash stations.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Chemical safety goggles/faceshield. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection

Wear suitable protective clothing. Rubber, neoprene, or other impervious gloves are recommended to prevent skin contact. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task. Reference Wiley's "Quick Selection Guide to Chemical Protective Clothing". Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection

Ensure adequate ventilation, especially in confined areas. For spray application, a NIOSH approved dust respirator and eye protection. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Paste	Odor	None
Appearance	White paste	Odor Threshold	Not determined
Color	White		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	12	
Melting point / freezing point	Not determined	
Boiling point / boiling range	> 100 °C / 212 °F	
Flash point	None	
Evaporation Rate	Same as water	
Flammability (Solid, Gas)	Not determined	
Flammability Limit in Air		
Upper flammability or explosive limits	Not determined	
Lower flammability or explosive limits	Not determined	
Vapor Pressure	Same as water	
Vapor Density	Same as water	
Relative Density	Not determined	
Water Solubility	Completely soluble	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition temperature	Not determined	
Decomposition temperature	Not determined	
Kinematic viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

Other information

VOC Content (%) 50%

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

Acids. Organic halogen compounds. Nitromethane. Flammable liquid. Metals such as aluminum, tin, and zinc.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Avoid contact with eyes.
Skin Contact	Avoid contact with skin.
Inhalation	Avoid breathing vapors or mists. May cause irritation of respiratory tract.
Ingestion	May be harmful if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Calcium Hydroxide	= 7340 mg/kg (Rat)	> 2500 mg/kg (Rat)	-
Sodium hydroxide	= 325 mg/kg (Rat)	= 1350 mg/kg (Rabbit)	-
Proprietary 1	= 27000 mg/kg (Rat)	-	> 5800 mg/m ³ (Rat) 4 h
Proprietary 3	= 1219 mg/kg (Rat)	-	-
Proprietary 4	= 4090 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	May cause dermatitis or irritation in some individuals upon prolonged contact. May cause severe chemical burns with reddening and pain. May cause skin and eye irritation. May cause irritation to the mucous membranes and upper respiratory tract. May cause burns to mouth and gastrointestinal corrosion.
-----------------	---

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Causes severe skin burns.
Serious eye damage/eye irritation	Causes severe eye damage.

Carcinogenicity

This ingredient is a possible carcinogen when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Proprietary 2	A2	Group 1	Known	X

Legend**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

STOT - repeated exposure

Respirable crystalline silica causes damage to organs (lung effects, immune system effects, and kidney effects) through prolonged or repeated exposure.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50 3,852.6 mg/kg

Dermal LD50 6,127.0 mg/kg

12. ECOLOGICAL INFORMATION**Ecotoxicity**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Sodium hydroxide 1310-73-2		45.4: 96 h Oncorhynchus mykiss mg/L LC50 static	

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Calcium Hydroxide 1305-62-0	Corrosive
Sodium hydroxide 1310-73-2	Toxic Corrosive

14. TRANSPORT INFORMATION

Note Based on package size, product may be eligible for limited quantity exception.

DOT

UN/ID No UN1823
 Proper Shipping Name Sodium hydroxide, solid, mixture
 Hazard class 8
 Packing Group II

IATA

UN number UN1823
 Proper Shipping Name Sodium hydroxide, solid, mixture
 Transport hazard class(es) 8
 Packing Group II

IMDG

UN number UN1823
 Proper Shipping Name Sodium hydroxide, solid, mixture
 Transport hazard class(es) 8
 Packing Group II

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
Calcium Hydroxide	X	ACTIVE	X	X	X	X	X	X	X
Sodium hydroxide	X	ACTIVE	X	X	X	X	X	X	X
Proprietary 1	X	ACTIVE	X		X	X	X	X	X
Silica, Quartz	X	ACTIVE	X	X	X	X	X	X	X
Proprietary 2	X	ACTIVE	X	X	X	X	X	X	X
Proprietary 3	X	ACTIVE	X	X		X	X	X	X
Proprietary 4	X	ACTIVE	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Sodium hydroxide 1310-73-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium hydroxide	1000 lb			X

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Silica, Quartz	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Calcium Hydroxide 1305-62-0	X	X	X
Sodium hydroxide 1310-73-2	X	X	X
Silica, Quartz 14808-60-7	X	X	X

16. OTHER INFORMATION**NFPA****Health Hazards****Flammability****Instability****Special Hazards****HMIS****Health Hazards****Flammability****Physical hazards****Personal Protection**

3

0

0

Not determined

Issue Date:

01-Jan-2008

Revision Date:

17-Apr-2023

Revision Note:

Regulatory update

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet